

SMART MINING STROBE



FEATURES



6 SUPER
BRIGHT
RGBW LEDS



4
OPERATING
MODE INPUTS



9-50VDC
OPERATING
VOLTAGE



NO MOVING
PARTS &
FLEXIBLE
MOUNTING



LOW
POWER
CONSUMPTION



SUPPORTS
POSITIVE &
NEGATIVE
MASTER SWITCH



12,000
mAh BATTERY
BACKUP



EASY
INSTALLATION



LONG
SERVICE
LIFE



BLE
ENABLED



AUTO
RECHARGE



HEAVY
DUTY

TECHNICAL SPECIFICATIONS

DESCRIPTION	MIN	NOM	MAX	UNIT
INPUT VOLTAGE	10		50	V
CURRENT CONSUMPTION			6.3	A
BATTERY VOLTAGE		3.2		V
BATTERY CAPACITY		12		Ah
WEIGHT		1.5		Kg
MOUNTING HOLE SIZE		5/16		Inch
MOUNTING HOLE SIZE		7.93		mm
IP RATING		65		IP
OPERATING TEMPERATURE		-40	50	C°
CONNECTOR	Built-in Deutsch DT-6 (6-pin)			
BODY/HOUSING	Polycarbonate with stainless-steel			

THIS PRODUCT IS PROTECTED BY US PATENT No. 10482729 AND CANADIAN PATENT No. 2,987,350 BY ITS INVENTOR PAUL TONELLO. ALL RIGHTS RESERVED.