

# SMART MINING STROBE



## FEATURES



**6** SUPER  
BRIGHT  
RGBW LEDS



**4**  
OPERATING  
MODE INPUTS



**9-50**VDC  
OPERATING  
VOLTAGE



NO MOVING  
PARTS &  
FLEXIBLE  
MOUNTING



**LOW**  
POWER  
CONSUMPTION



SUPPORTS  
POSITIVE &  
NEGATIVE  
MASTER SWITCH



**12,000**  
mAh BATTERY  
BACKUP



**EASY**  
INSTALLATION



**LONG**  
SERVICE  
LIFE



FULLY  
PROGRAMMABLE  
& BLE ENABLED



**AUTO**  
RECHARGE



**HEAVY**  
DUTY

## TECHNICAL SPECIFICATIONS

DESCRIPTION	MIN	NOM	MAX	UNIT
INPUT VOLTAGE	10		50	V
CURRENT CONSUMPTION			6.3	A
BATTERY VOLTAGE		3.2		V
BATTERY CAPACITY		12		Ah
WEIGHT		1.5		Kg
MOUNTING HOLE SIZE		5/16		Inch
MOUNTING HOLE SIZE		7.93		mm
IP RATING		65		IP
OPERATING TEMPERATURE		-40	50	C°
CONNECTOR	Built-in Deutsch DT-6 (6-pin)			
BODY/HOUSING	Polycarbonate with stainless-steel			

THIS PRODUCT IS PROTECTED BY US PATENT No. 10482729 AND CANADIAN PATENT No. 2,987,350 BY ITS INVENTOR PAUL TONELLO. ALL RIGHTS RESERVED.